

GLOBE POST TOP FIXTURE 2003/8003



Wave Lighting's Residential Globe Fixture is ideal for any outdoor patio or walkway. This fixture is available in incandescent with A19 LED lamp option and is easily relamped via 2 screws in fitter. This fixture can be used to comply with 2016 Title 24 Part 6 High Efficacy LED Light Source Requirements. Wave Lighting's 16" Dia. Globe fits on a 3" diameter pole (sold separately) only mounting hardware is included.

LED SOURCE OPTIONS

E26 REPLACEABLE LED - LE26

- 120V, 50/60Hz
- "Screw-In" Medium Base A19/E26 LED Lamp
- Estimated 15,000 Hrs L₇₀
- Low Flicker (3K models)
- Dimmable (see compatible dimmer list)
- 3000K CCT 90CRI or 4000K CCT 80CRI
- 3 Year Warranty

REPLACEABLE LED CORN COB - LC

- 100-277V, 50/60Hz
- 250W Metal Halide Equivalent Lamp Included
- E39 Mogul Base Socket
- Estimated 50,000 Hrs L₇₀
- Surge Supression
- Available in 4000K CCT 80CRI
- Type 5 Type 5, or Dark Sky Distribution
- 5 Year Warranty
- DLC Listed

HIGH PRESSURE SODIUM - 70H

- HPF Integral Magnetic Ballast, 120V
- 70W Lamp Included
- 4kV Medium Base Socket
- 1 Year Warranty

SPECIFICATIONS

- Cast Aluminum or Polycarbonate Fitters
- Black, White, or Bronze (Aluminum Only)
- Post Mount Only
- Polycarbonate or Acrylic Globe Diffuser
- Clear, Opal, Smoke or Clear Prism Diffuser Options
- UL Listed For Wet Locations

GUIDE: 8003PR-BZ

CALL FOR PHOTOMETRIC INFORMATION

ITEM #	GLOBE	LIGHT SOURCE	FITTER MATERIAL
2003-16" DIA	POLYCARBONATE Opal CL-Clear SM-Smoke	INCANDESCENT (1) 150W MAX Medium Base	POWDERCOATED CAST ALUMINUM Black BZ-Bronze WH-White
		HIGH PRESSURE SODIUM 70H-(1) 70W 4Kv Medium Base ☆	
		LED LIGHT SOURCE	
8003-16" DIA	ACRYLIC Opal CL-Clear SM-Smoke PR-Clear Prismatic	E26 MEDIUM BASE LED LE26-10W 800lm ☆	POLYCARBONATE BP-Black WP-White
			CCT C-4K W-3K
		REPLACEABLE LED CORN COB LC5- 24W 3120lm Type 5 ☆ LC3- 20W 3000lm Type 3 ☆ LCD- 24W 2400lm Dark Sky ☆	C-4K

☆ Lamp Included

REFER TO CATALOG FOR OPTION SPECIFICATIONS - Specifications subject to change without notice - FIXTURE SPEC 1/19