



Cylinder Aluminum Housing



S64FM
Ceiling Mount



S64W
Downlight
EXTENDS: 7 3/4"
H/CTR: 2 3/8"
BACKPLATE:
4 5/8" X 4 5/8"



S65W
Up & Downlight
EXTENDS: 7.75"
H/CTR: 6.875"
BACKPLATE:
4.625" X 4.625"

GUIDE: S65W-LR12W-BK

ITEM #	LED LIGHT SOURCE	CCT	COLOR
S64W S64FM	120V LIGHTWAVE LED	C-4K	BK-Black
	LR12-13W 1000lm 80CRI	W-3K	BZ-Bronze
S65W	LR12-2x13W 2000lm 80CRI		

See page 31 for composite version.




Citadel Enclosed & Gasketed

- Occupancy sensor available
 - Emergency backup available
 - Die cast aluminum
 - IP65 rated
- (see cut sheet for more information)



166FM
Ring



← 11.80" Diam →
H/CTR: 5 7/8"



169FM
Eyelid

GUIDE: 166FMF-LR15C-BK

ITEM #	DIFFUSER	LED LIGHT SOURCE	CCT	COLOR	OPTIONS
166FM 169FM	POLYCARBONATE F-Frosted	120V LIGHTWAVE LED	C-4K	BK-Black WH-White	EB-Emergency Backup O-Occupancy Sensor (options cannot be combined) options are not available with LR32 & LT32 light source
		LR15-15W 1400lm 80CRI ★	W-3K		
		LR22-23W 1900lm 80CRI ★			
		LR32-32W 2700lm 80CRI			
		LT15-16W 1400lm 90CRI			
		LT22-24W 2020lm 90CRI			
		LT32-32W 2700lm 90CRI			
		120-277V MULTI-VOLT			
		L22-22W 1824lm	4K		

† Lamp included. ★ Energy Star qualified product. Options can not be combined. Spec sheets and IES files available online. Specifications subject to change without notice. LED option information on page 5.

