


POST TOP FIXTURE C92T

COMMERCIAL POST LIGHTING



EPA 1.085ft²
WT 18lbs

IES FILES AVAILABLE ONLINE AT WAVELIGHTING.COM

Wave Lighting's commercial product line provides safety and security for all types of applications including parks, pedestrian walkways, and parking areas. Our Post top fixtures fit on any standard 3" diameter commercial pole (sold separately) with 3 set screws and allen wrench (provided). Standard 8" fitter neck acorn diffuser is easily removed by loosening 3 set screws (provided).

LIGHT SOURCE OPTIONS

DEDICATED LED SYSTEM - L

- 120-277V, 50/60Hz
- 150W or 250W Metal Halide Equivalent
- Estimated 100,000 Hrs L₈₀
- Surge Supression
- 3000K*, 4000K, or 5000K* CCT, 80CRI
- Type 3* or Type 5 Distribution
- 0 - 10V Dimming
- 5 Year Warranty
- DLC Listed

REPLACEABLE LED CORN COB - LC

- 100-277V, 50/60Hz
- 250W Metal Halide Equivalent Lamp Included
- E39 Mogul Base Socket
- Estimated 50,000 Hrs L₇₀
- Surge Supression
- Available in 4000K CCT 80CRI
- Type 3, Type 5, or Dark Sky Distribution
- 5 Year Warranty
- DLC Listed

HID SYSTEM - MH/H

- Multi-Tap Magnetic Ballast, 120-277V Option
- Metal Halide or High Pressure Sodium
- Up To 150W Lamp Included
- 4kV Medium Base Socket, Mogul On Request
- Type 3, Type 5, or Dark Sky Friendly Distribution
- 1 Year Warranty



SPECIFICATIONS

- Cast Aluminum Housing
- Stainless Steel Set Screws
- Black, White, or Bronze Finish
- Polycarbonate or Acrylic Acorn Diffuser
- Clear, Opal or Frost Diffuser Options
- UL Listed For Wet Locations

GUIDE: C92TCA-L40C-BK

CALL FOR PHOTOMETRIC INFORMATION

ITEM #	ACORN	LIGHT SOURCE	COLOR	HID OPTIONS	
C92T	POLYCARBONATE C -Clear Textured ACRYLIC LA -Opal Textured CA -Clear Textured FA -Frost Textured	INCANDESCENT (1) 200W MAX Medium Base HPF MAGNETIC BALLAST 100MH -(1) 100W Metal Halide ☆ 150MH -(1) 150W Metal Halide ☆ 70H -(1) 70W HPS ☆ 100H -(1) 100W HPS ☆ 150H -(1) 150W HPS ☆	BK -Black BZ -Bronze WH -White	DSR -Dark Sky Reflector HS -House Shield MG -Mogul Socket MT -Multi-Tap (Specify 208, 240, or 277v. Tapped at 120v by default) R3 -Type III Glass Refractor R5 -Type V Glass Refractor	
		LED LIGHT SOURCE			
		DEDICATED LED SYSTEM L40 -40W 4000lm L60 -60W 6000lm REPLACEABLE LED CORN COB LC3 -Type 3, 40W 5600lm ☆ LC5 -Type 5, 54W 7200lm ☆ LCD -Dark Sky, 54W 5900lm ☆			CCT W -3K* C -4K B -5K*

* Special order item. Longer lead times may apply. Option not available in Replaceable Corn Cob model. ☆ Lamp Included