

PROJECT		
TYPE		
VOLTAGE		

INDOOR CEILING FIXTURE 168FM

INDOOR DECORATIVE













SPECIFICATIONS

- Brushed Nickel Hosuing
- Mounting Hardware Included
- White Acrylic Diffuser
- Minimum Starting Temp -20°F
- UL Listed for Damp Locations

Wave Lighting's 168FM adds a contemporary look to any interior space. This fixture is available in incandescent and LED and is easily relamped by unscrewing diffuser from base. Wave Lighting's 168FM is designed for ceiling applications and mounting hardware is included. Options include pendant mount kit and an occupancy sensor.

LED SOURCE OPTIONS

LIGHTWAVE LED - LR/LT

- 120V, 50/60 Hz
- AC Driver-On-Board Array
- Estimated 50,000 Hrs L_{70}
- Low Flicker (LT models)⁷
- Surge Supression
- Dimmable (see compatible dimmer list)
- High Efficacy LED Light Source
- 3000K CCT 90CRI or 4000K CCT 80 CRI
- 5 Year Warranty
- Energy Star

LED MULTI-VOLT SYSTEM - L22

- 120-277V, 50/60Hz
- Estimated 50,000 Hrs L₇₀
- 3000K CCT 80CRI
- 3 Year Warranty
- Energy Star

E26 MEDIUM BASE - LE26

- 120V, 50/60Hz
- "Screw-In" Medium Base A19/E26 LED Lamp
- \bullet Estimated 15,000 Hrs L_{70}
- Low Flicker (3K models)
- Dimmable (see compatible dimmer list)
- 3000K CCT 90CRI or 4000K CCT 80 CRI
- 3 Year Warranty
- Energy Star

GUIDE CODE: 168FM-LR12C-BN-OS CALL FOR PHOTOMETRIC INFORMATION

ITEM#	LENS	LIGHT SOURCE	ССТ	COLOR	OPTIONS
168FM ACRYL White	ACRYLIC White	E26 MEDIUM BASE LED	C -4K W -3K	BN -Brush Nickel	PK-Pendant Kit OS-Occupancy Sensor (options not available with LR32 or LT32)
		2LE26 -9.5W 800lm (E26 LED Lamp) ★ ★ (2) 40W MAX Medium Base			
		120V LIGHTWAVE LED			
		LR15-15W 1400Im 80CRI ★ LR22-23W 1900Im 80CRI ★ LR32-32W 2700Im 80CRI LT15-16W 1400Im 90CRI LT22-24W 2020Im 90CRI LT32-32W 2700Im 90CRI			
		120-277V MULTI-VOLT LED			
		L22 -22W 1704lm 80CRI ★	3K		

⁺ Lamp included. ★Energy Star qualified product. Mounting kits ship in separate packaging. Assembly required.