

PROJECT		

VOLTAGE

TYPE

OUTDOOR POST FIXTURE 113/114

OUTDOOR DECORATIVE MARLEX*

Wave Lighting's 113/114 adds a welcoming look to any outdoor space. Wave Lighting's 113/114 fits on a 3" diameter pole (sold separately) mounting



OOMI EIANTI







LED SOURCE OPTIONS

LIGHTWAVE LED - LR/LT

• 120V, 50/60 Hz

hardware is included.

- AC Driver-On-Board Array
- Estimated 50,000 Hrs L_{70}
- Low Flicker (LT models)
- Surge Supression
- Dimmable (see compatible dimmer list)
- High Efficacy LED Light Source
- 3000K or 4000K CCT 80 or 90CRI
- 5 Year Warranty

E26 MEDIUM BASE - LE26

- 120V, 50/60Hz
- "Screw-In" Medium Base A19/E26 LED Lamp
- Estimated 15,000 Hrs L_{70}
- Low Flicker (3K models)
- Dimmable (see compatible dimmer list)
- 3000K CCT 90CRI or 4000K CCT 80CRI
- 3 Year Warranty

SPECIFICATIONS

- Black or White
- Mounting Hardware Included
- Clear, Amber or Frosted Acrylic Diffuser
- Post Mount Only
- Minimum Starting Temp -20°F
- UL Listed for Wet Locations
- Composite Construction
- Non-Corrosive





GUIDE CODE: 113-LR12W

CALL FOR PHOTOMETRIC INFORMATION

ITEM#	LENS	LIGHT SOURCE	сст
113 -White 114 -Black	ACRYLIC Clear Beveled A-Amber Beveled Diamond C-Clear Beveled Diamond F-Frosted Beveled	E26 MEDIUM BASE	C- 4K W- 3K
		(1) 75W MAX Medium Base LE26 -9.5W 800lm (E26 LED Lamp) +	
		120V LIGHTWAVE LED	
		LR12-13W 1000Im 80CRI LR15-15W 1400Im 80CRI LR22-23W 1900Im 80CRI LT12-12W 1040Im 90CRI LT15-16W 1400Im 90CRI LT22-24W 2020Im 90CRI	

⁺ Lamp included.