


PROJECT		
TYPE		

OUTDOOR WALL FIXTURE S771WF

OUTDOOR DECORATIVE MARLEX®





SPECIFICATIONS

- · Black or White
- Mounting Hardware Included
- Frosted Polycarbonate Diffuser
- Wall Mount Only
- Minimum Starting Temp -20°F
- UL Listed for Wet Locations
- Composite Construction
- Non-Corrosive





GUIDE CODE: S771WF-LR12W-WH-PC

Wave Lighting's S771WF adds a contemporary look to any outdoor space. Wave Lighting's S771WF is designed for wall applications and mounting hardware is included. Options include photocell.



VOLTAGE











LED SOURCE OPTIONS

LIGHTWAVE LED - LR/LT

- 120V, 50/60 Hz
- AC Driver-On-Board Array
- Estimated 50,000 Hrs L_{70}
- Low Flicker (LT models)
- Surge Supression
- Dimmable (see compatible dimmer list)
- High Efficacy LED Light Source
- 3000K or 4000K CCT 80 or 90CRI
- 5 Year Warranty
- Energy Star

LED MULTI-VOLT SYSTEM - L11

- 120-277V, 50/60Hz
- Estimated 50,000 Hrs L_{70}
- 4000K CCT 80CRI
- 3 Year Warranty

E26 MEDIUM BASE - LE26

- 120V, 50/60Hz
- "Screw-In" Medium Base A19/E26 LED Lamp
- Estimated 15,000 Hrs L_{70}
- Low Flicker (3K models)
- Dimmable (see compatible dimmer list)
- 3000K CCT 90CRI or 4000K CCT 80CRI
- 3 Year Warranty
- Energy Star

CALL FOR PHOTOMETRIC INFORMATION

ITEM#	DIFFUSER	LIGHT SOURCE	сст	COLOR	OPTIONS
S771W POLYCARBONATE F-Frosted Ribbon		E26 MEDIUM BASE	C -4K	BK -Black WH -White	PC-Photocell (120V Lightwave LED only)
	F -Frosted Ribbon	POLYCARBONATE BACK PAN (1) 60W MAX Medium Base LE26-9.5W 800lm (E26 LED Lamp) + *	W -3K		
	120V LIGHTWAVE LED				
		ALUMINUM BACK PAN_ LR12-13W 1000Im 80CRI ★ LT12-12W 1040Im 90CRI			
		120-277V MULTI-VOLT LED			
		L11 -11W 912lm	4K		

⁺ Lamp included. ★Energy Star qualified product.