

PROJECT		
TYPE		

GUARDIAN ROUND WALL/CEILING MOUNT 165FM

OUTDOOR DECORATIVE MARLEX®



Wave Lighting's 165FM adds a contemporary look to any outdoor space. Wave Lighting's 165FM is designed for ceiling applications and mounting hardware is included. Options include Emergency Backup and Occupancy Sensor.



VOLTAGE













LED SOURCE OPTIONS

LIGHTWAVE LED - LR/LT

- 120V, 50/60 Hz
- AC Driver-On-Board Array
- \bullet Estimated 50,000 Hrs L_{70}
- Low Flicker (LT models)
- Surge Supression
- Dimmable (see compatible dimmer list)
- High Efficacy LED Light Source
- 3000K or 4000K CCT 80 or 90CRI
- 5 Year Warranty
- Energy Star

LED MULTI-VOLT SYSTEM - L22

- 120-277V, 50/60Hz
- Estimated 50,000 Hrs L₇₀
- 4000K CCT 80CRI
- 3 Year Warranty

E26 MEDIUM BASE LED - LE26

- 120V, 50/60Hz
- "Screw-In" Medium Base A19/E26 LED Lamp
- Estimated 15,000 Hrs L_{70}
- Low Flicker (3K models)
- Dimmable (see compatible dimmer list)
- 3000K CCT 90CRI or 4000K CCT 80CRI
- 3 Year Warranty

GUIDE CODE: 165FM-LR22W-WH

SPECIFICATIONS

• Black or White Finish

Opal Diffuser

Non-Corrosive

BK BLACK

Knockouts For Conduit

Ceiling and Wall Mount

Mounting Hardware Included

• Minimum Starting Temp -20°F

• UL Listed for Wet Locations

WH WHITE

Bug and Tamper Resistant Design

CALL FOR PHOTOMETRIC INFORMATION

ITEM#	DIFFUSER	LIGHT SOURCE	ССТ	COLOR	OPTIONS
165FM POLYCARBONATE Opal		E26 MEDIUM BASE LED		BK -Black	PC-Photocell
	(2) 60W MAX Medium Base 2LE26 - (2) 9.5W 800lm (E26 LED Lamp) +	W -3K	WH-White	O-Occupancy Sensor EB-Emergency Backup (EB for 120V Lightwave &	
	120V LIGHTWAVE LED		120-277 Multi-Volt LED only)		
	LR12-13W 1000lm 80CR ★ LR15-15W 1400lm 80CRI ★ LR22-23W 1900lm 80CRI ★ LT12-12W 1000lm 90CRI LT15-16W 1400lm 90CRI LT22-24W 1900lm 90CRI			(options cannot be combined)	
		120-277V MULTI-VOLT LED			
		L22- 22W 1824lm	4K		

⁺ Lamp included. ★Energy Star qualified product.