

PROJECT		

VOLTAGE

**TYPE** 

## **OUTDOOR WALL FIXTURE 215**

## **OUTDOOR DECORATIVE MARLEX**



**SPECIFICATIONS** 

Clear Glass DiffuserWall Mount Only

Mounting Hardware Included

• Minimum Starting Temp -20°F

• UL Listed for Wet Locations


WH WHITE

· Black or White

Non-Corrosive

BK BLACK

EXTENDS: 5 7/8"
H/CTR: 2 3/8"
BACKPLATE: 4 3/4" x 4 1/2"



Wave Lighting's 215 adds a contemporary look to any outdoor space. Wave Lighting's 215 is designed for wall applications and mounting hardware is included. Options include photocell.













# LED SOURCE OPTIONS

#### LIGHTWAVE LED - LR/LT

- 120V, 50/60 Hz
- AC Driver-On-Board Array
- Estimated 50,000 Hrs  $L_{70}$
- Low Flicker (LT models)
- Surge Supression
- Dimmable (see compatible dimmer list)
- High Efficacy LED Light Source
- 3000K or 4000K CCT 80 or 90CRI
- 5 Year Warranty
- Energy Star

#### **LED MULTI-VOLT SYSTEM - L11**

- 120-277V, 50/60Hz
- Estimated 50,000 Hrs L<sub>70</sub>
- 4000K CCT 80CRI
- 3 Year Warranty

## **E26 MEDIUM BASE - LE26**

- 120V, 50/60Hz
- "Screw-In" Medium Base A19/E26 LED Lamp
- Estimated 15,000 Hrs  $L_{70}$
- Low Flicker (3K models)
- Dimmable (see compatible dimmer list)
- 3000K CCT 90CRI or 4000K CCT 80CRI
- 3 Year Warranty
- Energy Star

# GUIDE CODE: 215-WH-LR12C-PC

#### **CALL FOR PHOTOMETRIC INFORMATION**

ITEM#	GLOBE/JAR	COLOR	LIGHT SOURCE	ССТ	OPTIONS
215	GLASS Clear Ribbed	<b>BK</b> -Black <b>WH</b> -White	E26 MEDIUM BASE	<b>C</b> -4K <b>W</b> -3K	PC-Photocell (120V only)
			(1) 60W MAX Medium Base <b>LE26</b> -9.5W 800lm (E26 LED Lamp) + *		
			120V LIGHTWAVE LED		
			<b>LR12</b> -13W 1000lm 80CRI ★ <b>LT12</b> -12W 1040lm 90CRI		
			120-277V MULTI-VOLT LED		
			<b>L11</b> -11W 912Im	4K	

<sup>+</sup> Lamp included. ★Energy Star qualified product.