



Wave Lighting's 163FM adds a contemporary look to any interior space. This fixture is available in incandescent and LED and is easily relamped by removing 3 thumb screws (included) from base. This fixture can be used to comply with 2016 Title 24 Part 6 High Efficacy LED Light Source Requirements. Wave Lighting's 163FM is designed for ceiling or wall applications and mounting hardware is included. Options include occupancy sensor.

### LED SOURCE OPTIONS

#### LIGHTWAVE LED - LR/LT

- 120V, 50/60 Hz
- AC Driver-On-Board Array
- Estimated 50,000 Hrs L<sub>70</sub>
- Low Flicker (LT models)
- Surge Supression
- Dimmable (see compatible dimmer list)
- High Efficacy LED Light Source
- 3000K or 4000K CCT; 80\*\* or 90CRI
- 5 Year Warranty
- Energy Star

#### LED MULTI-VOLT SYSTEM - L22

- 120-277V, 50/60Hz
- Estimated 50,000 Hrs L<sub>70</sub>
- 3000K CCT 80CRI
- 3 Year Warranty
- Energy Star

#### E26 REPLACEABLE LED - LE26

- 120V, 50/60Hz
- "Screw-In" Medium Base A19/E26 LED Lamp
- Estimated 15,000 Hrs L<sub>70</sub>
- Low Flicker (3K models)
- Dimmable (see compatible dimmer list)
- 3000K CCT 90CRI or 4000K\*\* CCT 80CRI
- 3 Year Warranty
- Energy Star



### SPECIFICATIONS

- White Powder Coated Finish
- Mounting Hardware Included
- White Acrylic Diffuser
- Wall or Ceiling Mount
- Minimum Starting Temp -20°F
- UL Listed for Damp Locations

### GUIDE: 163FM-LR15C-WH

### CALL FOR PHOTOMETRIC INFORMATION

ITEM #	LENS	LIGHT SOURCE	COLOR	OPTION	
163FM	ACRYLIC White	INCANDESCENT (2) 40W MAX Medium Base	WH-White	OS-Occupancy Sensor*	
		LED LIGHT SOURCE			
		LIGHTWAVE LED			CCT C-4K W-3K
		LR15-15W 1400lm 80CRI  **			
		LR22-23W 1900lm 80CRI  **			
		LR32-32W 2700lm 80CRI  **			
		LT15-16W 1400lm 90CRI			
LT22-24W 2020lm 90CRI					
LED MULTI-VOLT SYSTEM	3K				
E26 REPLACEABLE LED	C-4K** W-3K				
2LE26-(2) 10W 800lm  ☆					

\*Use of OS option voids Energy Star Qualification. \*\* Not JAB Compliant. ☆ Lamp Included Energy Star Qualified Product