


PROJECT		
TYPE		
VOLTAGE		

## **OUTDOOR SECURITY FIXTURE 265FMF OUTDOOR DECORATIVE MARLEX**



4 1/2"





# **SPECIFICATIONS**

- White Powdercoated Aluminum
- Mounting Hardware Included
- Frosted Prismatic Diffuser
- Wall or Ceiling Mount
- Minimum Starting Temp -20°F
- UL Listed for Wet Locations
- Non-Corrosive

Wave Lighting's 265FMF adds a welcoming look to any outdoor space. Wave Lighting's 265FMF is designed for wall or ceiling applications and mounting hardware is included. Options include occupancy sensor.













## LED SOURCE OPTIONS

### LIGHTWAVE LED - LR/LT

- 120V, 50/60 Hz
- AC Driver-On-Board Array
- Estimated 50,000 Hrs  $L_{70}$
- Low Flicker (LT models)
- Surge Supression
- Dimmable (see compatible dimmer list)
- High Efficacy LED Light Source
- 3000K or 4000K CCT 80 or 90CRI
- 5 Year Warranty
- Energy Star

### **E26 MEDIUM BASE - LE26**

- 120V. 50/60Hz
- "Screw-In" Medium Base A19/E26 LED Lamp
- Estimated 15,000 Hrs L<sub>70</sub>
- Low Flicker (3K models)
- Dimmable (see compatible dimmer list)
- 3000K CCT 90CRI or 4000K CCT 80CRI
- 3 Year Warranty
- Energy Star

#### **GUIDE CODE: 265FMF-LR12C-WH-O**

#### CALL FOR PHOTOMETRIC INFORMATION

ITEM#	DIFFUSER	LIGHT SOURCE	ССТ	COLOR	OPTIONS
265FM ACRYLIC F-Frosted Prisma	ACRYLIC <b>F</b> -Frosted Prismatic	E26 MEDIUM BASE	<b>C</b> -4K <b>W</b> -3K	<b>WH</b> -White	<b>O</b> -Occupancy Sensor
		(2) 40W MAX Medium Base <b>2LE26</b> -(2) 9.5W 800lm (E26 LED Lamp) <b>*</b>			
		120V LIGHTWAVE LED			
		LR15-15W 1400lm 80CRI ★ LR22-23W 1900lm 80CRI ★ LT15-16W 1400lm 90CRI LT22-24W 2020lm 90CRI			

<sup>+</sup> Lamp included. ★Energy Star qualified product.