



CEILING/WALL FIXTURE 166FM

COMMERCIAL LIGHTING



SCAN FOR VIDEO

Wave Lighting's 166FM adds a modern look to any outdoor space. This fixture is ETL Listed and IP65 rated. The 166FM is double gasketed with a twist-lock lens for a water and bug-proof tight seal. Wave Lighting's 166FM is designed for wall or ceiling applications and mounting hardware is included. Options include Emergency Backup with 135 minute runtime and Occupancy Sensor.



LED SOURCE OPTIONS

LIGHTWAVE LED - LR/LT

- 120V, 50/60 Hz
- AC Driver-On-Board Array
- Estimated 50,000 Hrs L₇₀
- Low Flicker (LT models)
- Surge Supression
- Dimmable (see compatible dimmer list)
- High Efficacy LED Light Source
- 3000K or 4000K CCT 80 or 90CRI
- 5 Year Warranty
- Energy Star

LED MULTI-VOLT SYSTEM - L22

- 120-277V, 50/60Hz
- Estimated 50,000 Hrs L₇₀
- Max 20kA Surge Supression
- 4000K CCT 80CRI
- 5 Year Warranty

SPECIFICATIONS

- Cast Aluminum Housing
- Mounting Hardware Included
- Black or White
- Frosted Polycarbonate Diffuser
- Wall or Ceiling Mount
- Minimum Starting Temp -20°F
- Hose Down - IP65 Rated
- ETL Listed for Wet Locations

BK BLACK

WH WHITE



GUIDE: 166FMF-LR15C-BK

CALL FOR PHOTOMETRIC INFORMATION

ITEM #	DIFFUSER	LED LIGHT SOURCE	CCT	COLOR	OPTIONS
166FM	POLYCARBONATE F-Frosted	120V LIGHTWAVE LED	C-4K W-3K	BK-Black WH-White	EB-Emergency Backup O-Occupancy Sensor (options cannot be combined) options are not available with LR32 & LT32 light source
		LR15-15W 1400lm 80CRI ★			
		LR22-23W 1900lm 80CRI ★			
		LR32-32W 2700lm 80CRI			
		LT15-16W 1400lm 90CRI			
		LT22-24W 2020lm 90CRI			
		LT32-32W 2700lm 90CRI			
		120-277V MULTI-VOLT			
		L22-22W 1824lm	4K		

† Lamp included. ★ Energy Star qualified product.