



WALL FIXTURE 169FM

COMMERCIAL LIGHTING



SCAN FOR VIDEO



Wave Lighting's 169FM adds a modern look to any outdoor space. This fixture is ETL Listed and IP65 rated. The 169FM is double gasketed with a twist-lock lens for a water and bug-proof tight seal. Wave Lighting's 169FM is designed for wall or ceiling applications and mounting hardware is included.



LED SOURCE OPTIONS

LIGHTWAVE LED - LR/LT

- 120V, 50/60 Hz
- AC Driver-On-Board Array
- Estimated 50,000 Hrs L₇₀
- Low Flicker (LT models)^o
- Surge Supression
- Dimmable (see compatible dimmer list)
- High Efficacy LED Light Source
- 3000K or 4000K CCT 80 or 90CRI
- 3 Year Warranty
- Energy Star

LED MULTI-VOLT SYSTEM - L22

- 120-277V, 50/60Hz
- Estimated 50,000 Hrs L₇₀
- Max 20kA Surge Supression
- 4000K CCT 80CRI
- 3 Year Warranty

SPECIFICATIONS

- Cast Aluminum Housing
- Mounting Hardware Included
- Black or White
- Frosted Polycarbonate Diffuser
- Wall Mount
- Minimum Starting Temp -20°F
- Hose Down - IP65 Rated
- ETL Listed for Wet Locations

BK BLACK

WH WHITE



GUIDE: 169FMF-LR15C-BK

CALL FOR PHOTOMETRIC INFORMATION

ITEM #	DIFFUSER	LED LIGHT SOURCE	CCT	COLOR	OPTIONS
169FM	POLYCARBONATE F-Frosted	120V LIGHTWAVE LED	C-4K W-3K	BK-Black WH-White	EB-Emergency Backup O-Occupancy Sensor (options cannot be combined) options are not available with LR32 & LT32 light source
		LR15-15W 1400lm 80CRI ★			
		LR22-23W 1900lm 80CRI ★			
		LR32-32W 2700lm 80CRI			
		LT15-16W 1400lm 90CRI			
		LT22-24W 2020lm 90CRI			
		LT32-32W 2700lm 90CRI			
		120-277V MULTI-VOLT			
		L22-22W 1824lm	4K		

★ Lamp included. ★Energy Star qualified product.